




Product Code	ASI-CHR-517233K
Description	Exposed Parts of Single Lever Built-in In-wall Manual Valve with Basin Spout (Compatible in wall parts ALA-509233 is sold separately)
Flow Rate	5.46 LPM @ 3 Bar
Recommended Water Pressure	1.0 Bar - 5 Bar
Material Composition Specification in Percentage	Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
Finish	Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (600 hrs + Validated) Adhesion (Pass)
Aerator Size	24 X 6
Available Colour Finishing	Black Chrome (BCH), Black Matt (BLM), Gold Bright PVD (GBP), Black Pearl PVD (BLP) & Blush Gold Bright PVD (BGP).
* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	